

## Spade Connectors Continued



### Non-Insulated - Butted Seam



Bare, Butted Seam - One piece, annealed, pure electrolytic copper construction with electro-tin plating for corrosion resistance. Deep internal serrations promote firm wire grip for maximum tensile strength.

Gauge	Stud Size	5PCS	50 PCS	100 PCS
22-18 AWG	#6		<b>2323-15</b>	<b>2323-16</b>
	#8		<b>2324-15</b>	<b>2324-CS</b>
	#10		<b>2325-15</b>	<b>2325-CS</b>
16-14 AWG	#6		<b>2423-15</b>	<b>2423-16</b>
	#8		<b>2424-15</b>	<b>2424-CS</b>
	#10		<b>2425-15</b>	<b>2425-CS</b>
12-10 AWG	#8	<b>2524-13</b>	<b>2524-15</b>	<b>2524-CS</b>
	#10	<b>2525-13</b>	<b>2525-15</b>	<b>2525-CS</b>



### Nylon Insulated RoHS

Nylon Insulated Spade Terminals provide superior insulation to vinyl. Insulation is securely molded and is flared for easier insertion. Allows for excellent mechanical crimp and wire strain relief.

Gauge	Stud Size	Mini Packs	50 PCS	100 PCS	1000 PCS
22-18 AWG	#6		<b>2923-15</b>	<b>2923-16</b>	
	#8		<b>2924-15</b>	<b>2924-16</b>	<b>2924-39</b>
	#10		<b>2925-15</b>	<b>2925-16</b>	<b>2925-39</b>
16-14 AWG	#6		<b>3023-15</b>	<b>3023-CS</b>	<b>3023-M</b>
	#8		<b>3024-15</b>	<b>3024-CS</b>	<b>3024-39</b>
	#10	<b>3025-BP 4 PCS</b>	<b>3025-15</b>	<b>3025-CS</b>	
12-10 AWG	#6		<b>3123-15</b>	<b>3123-16</b>	
	#8	<b>3124-BP 3 PCS</b>	<b>3124-15</b>	<b>3124-16</b>	
	#10	<b>3125-BP 3 PCS</b>	<b>3125-15</b>	<b>3125-16</b>	



### Flanged - Non-Insulated RoHS

Flanged configuration of the tang provides a positive lock to the post and increased pull-out force resistance.

Gauge	Stud Size	12 PCS	50 PCS	100 PCS
22-18 AWG	#6	<b>2333-13</b>		<b>2333-16</b>
	#8	<b>2334-13</b>		<b>2334-16</b>
	#10	<b>2335-13</b>		<b>2335-16</b>
16-14 AWG	#6	<b>2433-13</b>	<b>2433-15</b>	<b>2433-16</b>
	#8		<b>2434-15</b>	<b>2434-16</b>
	#10		<b>2435-15</b>	<b>2435-16</b>



### Flanged - Nylon Insulated RoHS

Nylon Insulated Spade Terminals provide superior insulation to vinyl. Insulation is securely molded and is flared for easier insertion. Allows for excellent mechanical crimp and wire strain relief. Flanged configuration of the tang provides a positive lock to the post and increased pull-out force resistance.

Gauge	Stud Size	50 PCS	100 PCS
22-18 AWG	#6	<b>2933-15</b>	<b>2933-CS</b>
	#8	<b>2934-15</b>	<b>2934-16</b>
	#10	<b>2935-15</b>	<b>2935-16</b>
16-14 AWG	#6	<b>3033-15</b>	<b>3033-CS</b>
	#8	<b>3034-15</b>	<b>3034-CS</b>
	#10	<b>3035-15</b>	<b>3035-CS</b>

## Ferrule Connectors



### Ferrule Connectors



Easy, clean and reliable. Ferrule Connectors provide exceptional connection of stranded wires. Adapted to Screw, Push-in and Spring Connections. Ferrule Connectors protect the stranded wire from fraying or being displaced when inserted.

Gauge	Length	Colour	100 PCS	500 PCS
22 AWG	6 MM	White	<b>10606-16</b>	<b>10606-38</b>
	8 MM	White	<b>10608-16</b>	<b>10608-38</b>
	10 MM	White	<b>10610-16</b>	<b>10610-38</b>
20 AWG	6 MM	Grey	<b>10706-16</b>	<b>10706-38</b>
	8 MM	Grey	<b>10708-16</b>	<b>10708-38</b>
	10 MM	Grey	<b>10710-16</b>	<b>10710-38</b>
18 AWG	6 MM	Red	<b>10712-16</b>	<b>10712-38</b>
	8 MM	Red	<b>10806-16</b>	<b>10806-38</b>
	10 MM	Red	<b>10808-16</b>	<b>10808-38</b>
16 AWG	6 MM	Red	<b>10810-16</b>	<b>10810-38</b>
	8 MM	Red	<b>10812-16</b>	<b>10812-38</b>
	10 MM	Red	<b>10812-16</b>	<b>10812-38</b>
14 AWG	8 MM	Black	<b>10908-16</b>	<b>10908-38</b>
	10 MM	Black	<b>10910-16</b>	<b>10910-38</b>
	12 MM	Black	<b>10912-16</b>	<b>10912-38</b>
	18 MM	Black	<b>10918-16</b>	<b>10918-38</b>
14 AWG	8 MM	Blue	<b>11008-16</b>	<b>11008-38</b>
	10 MM	Blue	<b>11010-16</b>	<b>11010-38</b>
	12 MM	Blue	<b>11012-16</b>	<b>11012-38</b>
	18 MM	Blue	<b>11018-16</b>	<b>11018-38</b>

Gauge	Length	Colour	100 PCS	500 PCS
12 AWG	10 MM	Grey	<b>11110-16</b>	<b>11110-38</b>
	12 MM	Grey	<b>11112-16</b>	<b>11112-38</b>
	18 MM	Grey	<b>11118-16</b>	<b>11118-38</b>
10 AWG	12 MM	Yellow	<b>11212-16</b>	<b>11212-38</b>
	18 MM	Yellow	<b>11218-16</b>	<b>11218-38</b>
8 AWG	12 MM	Red	<b>11312-16</b>	<b>11312-38</b>
	18 MM	Red	<b>11318-16</b>	<b>11318-38</b>
6 AWG	12 MM	Blue	<b>11412-36</b>	<b>11412-38</b>
	18 MM	Blue	<b>11418-36</b>	<b>11418-38</b>
4 AWG	16 MM	Yellow	<b>11516-36</b>	<b>11516-38</b>
2 AWG	18 MM	Red	<b>11618-36</b>	<b>11618-38</b>
1/0 AWG	20 MM	Blue	<b>11720-36</b>	
2/0 AWG	21 MM	Yellow	<b>11821-36</b>	
3/0 AWG	25 MM	Red	<b>11925-36</b>	
4/0 AWG	27 MM	Blue	<b>12027-36</b>	

