

## Quick Connectors



### Vinyl Insulated - Female

Injection molded vinyl with a funnel entry. High quality butted seam construction, pre-insulated with a polyvinyl chloride (PVC) sleeve. Insulation is colour-coded to NEMA standards and flared for easy insertion of both stranded and solid wire. PVC insulation provides support for the wire to avoid flexing at the point of crimp.

Gauge	Width	Mini Packs	50 PCS	100 PCS	1000 PCS
22-18 AWG	.110	<b>1749-BP</b> 9 PCS	<b>1749-15</b>	<b>1749-CS</b>	<b>1749-39</b>
	.187	<b>1751-BP</b> 9 PCS	<b>1751-15</b>	<b>1751-CS</b>	
	.250	<b>1755-BP</b> 9 PCS	<b>1755-15</b>	<b>1755-CS</b>	<b>1755-M</b>
16-14 AWG	.110	<b>1849-BP</b> 9 PCS	<b>1849-15</b>	<b>1849-CS</b>	<b>1849-39</b>
	.187	<b>1851-BP</b> 9 PCS	<b>1851-15</b>	<b>1851-CS</b>	
	.205	<b>1853-BP</b> 9 PCS	<b>1853-15</b>	<b>1853-CS</b>	
	.250	<b>1855-BP</b> 9 PCS	<b>1855-15</b>	<b>1855-CS</b>	<b>1855-M</b>
12-10 AWG	.250	<b>1955-BP</b> 6 PCS	<b>1955-15</b>	<b>1955-CP</b>	<b>1955-39</b>



### Vinyl Insulated - Male

Injection molded vinyl with a funnel entry. High quality butted seam construction, pre-insulated with a polyvinyl chloride (PVC) sleeve. Insulation is colour-coded to NEMA standards and flared for easy insertion of both stranded and solid wire. PVC insulation provides support for the wire to avoid flexing at the point of crimp.

Gauge	Width	Mini Packs	50 PCS	100 PCS	1000 PCS
22-18 AWG	.110	<b>1750-BP</b> 9 PCS	<b>1750-15</b>	<b>1750-CS</b>	
	.187	<b>1752-BP</b> 9 PCS	<b>1752-15</b>	<b>1752-CS</b>	
	.250	<b>1756-BP</b> 9 PCS	<b>1756-15</b>	<b>1756-CS</b>	
16-14 AWG	.110	<b>1850-BP</b> 9 PCS	<b>1850-15</b>	<b>1850-CS</b>	
	.187	<b>1852-BP</b> 9 PCS	<b>1852-15</b>	<b>1852-CS</b>	
	.250	<b>1856-BP</b> 9 PCS	<b>1856-15</b>	<b>1856-CS</b>	<b>1856-39</b>
12-10 AWG	.250	<b>1956-BP</b> 6 PCS	<b>1956-15</b>	<b>1956-CP</b>	



### Nylon Fully Insulated Double Bump - Female

Gauge	Width	3 PCS	50 PCS	100 PCS	1000 PCS
22-18 AWG	.250	<b>1765-BP</b>	<b>1765-15</b>	<b>1765-CP</b>	<b>1765-M</b>
16-14 AWG	.250	<b>1865-BP</b>	<b>1865-15</b>	<b>1865-CP</b>	<b>1865-M</b>
12-10 AWG	.250	<b>1965-BP</b>	<b>1965-15</b>	<b>1965-16</b>	<b>1965-M</b>



### Nylon Fully Insulated Double Bump - Male

Gauge	Width	3 PCS	50 PCS	100 PCS	1000 PCS
22-18 AWG	.250	<b>1764-BP</b>	<b>1764-15</b>	<b>1764-CP</b>	<b>1764-M</b>
16-14 AWG	.250	<b>1864-BP</b>	<b>1864-15</b>	<b>1864-CP</b>	<b>1864-M</b>
12-10 AWG	.250	<b>1964-BP</b>	<b>1964-15</b>	<b>1964-16</b>	<b>1964-M</b>



### Fully Insulated Oval Style - Female

 Vinyl / Nylon

Gauge	Width	Material	Mini Packs	50 PCS	100 PCS
22-18 AWG	.110	Vinyl		<b>2949-15</b>	<b>2949-16</b>
22-18 AWG	.187	Vinyl	<b>2951-13</b> 3 PCS	<b>2951-15</b>	<b>2951-16</b>
22-18 AWG	.250	Nylon		<b>2968-15</b>	<b>2968-16</b>
16-14 AWG	.110	Vinyl	<b>3049-13</b> 3 PCS	<b>3049-15</b>	<b>3049-16</b>
16-14 AWG	.187	Vinyl	<b>3051-13</b> 2 PCS	<b>3051-15</b>	<b>3051-16</b>
16-14 AWG	.250	Nylon	<b>3068-13</b> 2 PCS	<b>3068-15</b>	<b>3068-16</b>



### Nylon Insulated - Female

Gauge	Width	Mini Packs	50 PCS	100 PCS
22-18 AWG	.250	<b>2955-BP</b> 4 PCS	<b>2955-15</b>	<b>2955-CS</b>
16-14 AWG	.250	<b>3055-BP</b> 4 PCS	<b>3055-15</b>	<b>3055-CS</b>
12-10 AWG	.250	<b>3155-BP</b> 3 PCS	<b>3155-15</b>	<b>3155-16</b>



### Nylon Insulated - Male

Gauge	Width	Mini Packs	50 PCS	100 PCS
22-18 AWG	.250	<b>2956-BP</b> 4 PCS	<b>2956-15</b>	<b>2956-CS</b>
16-14 AWG	.250	<b>3056-BP</b> 4 PCS	<b>3056-15</b>	<b>3056-CS</b>
12-10 AWG	.250	<b>3156-BP</b> 3 PCS	<b>3156-15</b>	<b>3156-16</b>



### Nylon Fully Insulated Single Bump - Female

Butted Seam

Gauge	Width	3 PCS	10 PCS	100 PCS	1000 PCS
22-18 AWG	.250	<b>2065-13</b>	<b>2065-14</b>	<b>2065-16</b>	<b>2065-39</b>
16-14 AWG	.250	<b>2165-13</b>	<b>2165-14</b>	<b>2165-16</b>	<b>2165-39</b>
12-10 AWG	.250	<b>2265-13</b>	<b>2265-14</b>	<b>2265-16</b>	



### Nylon Fully Insulated Single Bump - Male

Butted Seam

Gauge	Width	3 PCS	10 PCS	100 PCS	1000 PCS
22-18 AWG	.250	<b>2064-13</b>	<b>2064-14</b>	<b>2064-16</b>	<b>2064-39</b>
16-14 AWG	.250	<b>2164-13</b>	<b>2164-14</b>	<b>2164-16</b>	<b>2164-39</b>
12-10 AWG	.250	<b>2264-13</b>	<b>2264-14</b>	<b>2264-16</b>	