

Quick Connectors Continued



Heat Shrink Insulated - Female RoHS

Translucent, Adhesive-Lined Polyolefin Tubing allows visual inspection, prevents wire corrosion and provides a waterproof seal. Conforms to automotive manufacturers' specifications for wiring repairs, necessary for maintaining electrical warranties.

Gauge	Width	5 PCS	25 PCS	100 PCS
22-18 AWG	.250	5855-BP	5855-15	5855-C
16-14 AWG	.250	5955-BP	5955-15	5955-C
12-10 AWG	.250	6055-BP	6055-15	6055-C



Heat Shrink Insulated - Male RoHS

Translucent, Adhesive-Lined Polyolefin Tubing allows visual inspection, prevents wire corrosion and provides a waterproof seal. Conforms to automotive manufacturers' specifications for wiring repairs, necessary for maintaining electrical warranties.

Gauge	Width	5 PCS	25 PCS	100 PCS
22-18 AWG	.250	5856-BP	5856-15	5856-C
16-14 AWG	.250	5956-BP	5956-15	5956-C
12-10 AWG	.250	6056-BP	6056-15	6056-C



Heat Shrink Fully Insulated - Female RoHS

Translucent, Adhesive-Lined Polyolefin Tubing allows visual inspection, prevents wire corrosion and provides a waterproof seal. Conforms to automotive manufacturers' specifications for wiring repairs, necessary for maintaining electrical warranties.

Gauge	Width	5 PCS	25 PCS	100 PCS
22-18 AWG	.250	5865-BP	5865-15	5865-C
16-14 AWG	.250	5965-BP	5965-15	5965-C
12-10 AWG	.250	6065-BP	6065-15	6065-C



Heat Shrink Fully Insulated - Male RoHS

Translucent, Adhesive-Lined Polyolefin Tubing allows visual inspection, prevents wire corrosion and provides a waterproof seal. Conforms to automotive manufacturers' specifications for wiring repairs, necessary for maintaining electrical warranties.

Gauge	Width	5 PCS	25 PCS	100 PCS
22-18 AWG	.250	5864-BP	5864-15	5864-36
16-14 AWG	.250	5964-BP	5964-15	5964-36
12-10 AWG	.250	6064-BP	6064-15	6064-36

Performance™

Crimp-Solder-Seal Quick Connectors

Crimped for mechanical reliability. Soldered for superior strength and conductivity. Sealed for maximum durability. Meets or exceeds the most stringent OEM standards.



Crimp-Solder-Seal - Female RoHS

Crimped for mechanical reliability. Soldered for superior strength and conductivity. Sealed for maximum durability. Meets or exceeds the most stringent OEM standards.



Gauge	Width	5 PCS	25 PCS	100 PCS
22-18 AWG	.250	3555-BP	3555-15	3555-36
16-14 AWG	.250	3655-BP	3655-15	3655-36
12-10 AWG	.250	3755-BP	3755-15	3755-36



Crimp-Solder-Seal - Male RoHS

Crimped for mechanical reliability. Soldered for superior strength and conductivity. Sealed for maximum durability. Meets or exceeds the most stringent OEM standards.



Gauge	Width	5 PCS	25 PCS	100 PCS
22-18 AWG	.250	3556-BP	3556-15	3556-36
16-14 AWG	.250	3656-BP	3656-15	3656-36
12-10 AWG	.250	3756-BP	3756-15	3756-36



Crimp-Solder-Seal Fully Insulated Female RoHS

Crimped for mechanical reliability. Soldered for superior strength and conductivity. Sealed for maximum durability. Meets or exceeds the most stringent OEM standards.



Gauge	Width	5 PCS	25 PCS	100 PCS
16-14 AWG	.250	3665-BP	3665-15	3665-36
12-10 AWG	.250	3765-BP	3765-15	3765-36

