

Quick Connectors Continued



.250 Volkswagen Open-End Piggyback

3 PCS	50 PCS	100 PCS
1597-BP	1597-15	1597-CS



.250 Volkswagen Quick Connect Splitter Splits 1-male tab into 2.

5 PCS	50 PCS	100 PCS
1591-BP	1591-15	1591-CS



.250 Volkswagen Quick Connect Splitter Splits 1-male tab into 2.

5 PCS	50 PCS	100 PCS
1594-BP	1594-15	1594-CS



.375 Volkswagen Quick Connector

Gauge	3 PCS	50 PCS	100 PCS
12-10 AWG	3157-BP	3157-15	3157-16



18-14 AWG Male GM Electronic Terminal Housing For use with Pico No. 1589

4 PCS	50 PCS
1862-13	1862-15



18-14 AWG Male GM Electronic Terminal Use with Pico No. 137 / 1862 OEM No. 2962987

2 PCS	10 PCS	50 PCS	100 PCS
1589-BP	1589-14	1589-15	1589-CS



Double Male Tab Connector For use with .250 Female Quick Connectors.

2 PCS	25 PCS	100 PCS
1257-13	1257-CS	1257-36



Double Plug Receptacle For use with .157 Bullet Connectors.

3 PCS	25 PCS	100 PCS
1260-BP	1260-CS	1260-36



Fuse Terminal GM Pack-Con III For use with Pico No. 945 (Page 72)

Gauge	2 PCS	25 PCS	100 PCS
16-14 AWG	1598-13	1598-15	1598-36



Parking & Tail Light Female Q/C Housing For use with Pico No. 1599

4 PCS	50 PCS	100 PCS
1863-13	1863-15	1863-36



Parking & Tail Light Female Q/C For use with Pico No. 1863

Gauge	2 PCS	50 PCS	100 PCS
16-14 AWG	1599-BP	1599-15	1599-CS

Bullets & Receptacles



Vinyl Insulated Bullets Injection Molded Vinyl Sleeve. High quality butted seam construction, pre-insulated with a polyvinyl chloride (PVC) sleeve. Insulation is colour-coded to NEMA standards and flared for easy insertion of both stranded and solid wire. PVC insulation provides support for the wire to avoid flexing at the point of crimp.

Gauge	Diameter	Mini Packs	50 PCS	100 PCS	1000 PCS
22-18 AWG	.157	1758-BP 7 PCS	1758-15	1758-CS	1758-39
22-18 AWG	.180	1759-BP 6 PCS	1759-15	1759-CS	1759-M
16-14 AWG	.157	1858-BP 6 PCS	1858-15	1858-CS	1858-39
16-14 AWG	.180	1859-BP 6 PCS	1859-15	1859-CS	
25 PCS					
12-10 AWG	.195	1958-BP 5 PCS	1958-15	1958-16	



Heat Shrink Insulated Bullets

Gauge	Diameter	5 PCS	25 PCS	100 PCS
16-14 AWG	.157	5958-BP	5958-15	5958-36



Vinyl Insulated Receptacles Injection Molded Vinyl Sleeve. High quality butted seam construction, pre-insulated with a polyvinyl chloride (PVC) sleeve. Insulation is colour-coded to NEMA standards and flared for easy insertion of both stranded and solid wire. PVC insulation provides support for the wire to avoid flexing at the point of crimp.

Gauge	Diameter	Mini Packs	50 PCS	100 PCS	1000 PCS
22-18 AWG	.157	1168-BP 7 PCS	1168-15	1168-CS	1168-39
22-18 AWG	.180	1169-BP 6 PCS	1169-15	1169-CS	1169-M
16-14 AWG	.157	1268-BP 6 PCS	1268-15	1268-CP	1268-39
16-14 AWG	.180	1269-BP 6 PCS	1269-15	1269-CS	
25 PCS					
12-10 AWG	.195	1368-BP 5 PCS	1368-CS	1368-16	



Heat Shrink Insulated Receptacles

Gauge	Diameter	5 PCS	25 PCS	100 PC
16-14 AWG	.157	5968-BP	5968-15	5968-36

