

Bullets & Receptacles Continued



Non-Insulated Bullets RoHS

Gauge	Diameter	50 PCS	100 PCS
16-14 AWG	.157	2458-15	2458-CS



Non-Insulated Receptacles RoHS

Gauge	Diameter	10 PCS	50 PCS	100 PCS
16-14 AWG	.157	2468-BP	2468-15	2468-CS



Nylon Insulated Bullets RoHS

Gauge	Diameter	4 PCS	50 PCS	100 PCS
22-18 AWG	.157	2958-13	2958-15	2958-16
16-14 AWG	.157	3058-15	3058-15	3058-16



Nylon Insulated Receptacles RoHS

Gauge	Diameter	4 PCS	50 PCS	100 PCS
22-18 AWG	.157	2957-13	2957-15	2957-16
16-14 AWG	.157	3057-13	3057-15	3057-16

Female Flag Connectors



High Temperature with Strain Relief RoHS

Recommended for use in ovens, motors, light fixtures and other applications where other connectors would corrode or melt. 900°F (482°C)

Gauge	Width	6 PCS	50 PCS	100 PCS
16-14 AWG	.250	9275-BP	9275-15	9275-CS



Non-Insulated with Strain Relief RoHS

Gauge	Width	5 PCS	50 PCS	100 PCS
16-14 AWG	.250	2775-BP	2775-15	2775-CS



Non-Insulated RoHS

Gauge	Width	Mini Packs	50 PCS	100 PCS
22-18 AWG	.250	2375-BP 9 PCS	2375-15	2375-CS
16-14 AWG	.205	2471-BP 9 PCS	2471-15	2471-CS
16-14 AWG	.250	2475-BP 9 PCS	2475-15	2475-CS
12-10 AWG	.250	2575-BP 3 PCS	2575-15	2575-CS



Nylon Insulated RoHS

Gauge	Width	3 PCS	50 PCS	100 PCS	1000 PCS
22-18 AWG	.250	2375N-BP	2375N-15	2375N-CS	2375N-39
16-14 AWG	.250	2475N-BP	2475N-15	2475N-CS	2475N-39
12-10 AWG	.250	2575N-BP	2575N-15	2575N-CS	2575N-39

Hook Connectors



Vinyl Insulated RoHS

Injection molded vinyl with a funnel entry. High quality butted seam construction, pre-insulated with a polyvinyl chloride (PVC) sleeve. Insulation is colour-coded to NEMA standards and flared for easy insertion of both stranded and solid wire. PVC insulation provides support for the wire to avoid flexing at the point of crimp.

Gauge	Stud Size	50 PCS	100 PCS
22-18 AWG	#6	1743-15	1743-16
22-18 AWG	#8	1744-15	1744-16
22-18 AWG	#10	1745-15	1745-16
16-14 AWG	#6	1843-15	1843-CS
16-14 AWG	#8	1844-15	1844-CS
16-14 AWG	#10	1845-15	1845-CS

Piggyback Connectors



Vinyl Insulated RoHS

Injection molded vinyl with a funnel entry. High quality butted seam construction, pre-insulated with a polyvinyl chloride (PVC) sleeve. Insulation is colour-coded to NEMA standards and flared for easy insertion of both stranded and solid wire. PVC insulation provides support for the wire to avoid flexing at the point of crimp.

Gauge	Width	5 PCS	50 PCS	100 PCS	1000 PCS
22-18 AWG	.250	1760-BP	1760-15	1760-16	1760-39
16-14 AWG	.250	1860-BP	1860-15	1860-CS	
12-10 AWG	.250	1960-BP	1960-15	1960-16	

Pin Connectors



Vinyl Insulated RoHS

Injection molded vinyl with a funnel entry. High quality butted seam construction, pre-insulated with a polyvinyl chloride (PVC) sleeve. Insulation is colour-coded to NEMA standards and flared for easy insertion of both stranded and solid wire. PVC insulation provides support for the wire to avoid flexing at the point of crimp.

Gauge	5 PCS	50 PCS	100 PCS	1000 PCS
22-18 AWG	1769-BP	1769-15	1769-16	1769-39
16-14 AWG	1869-BP	1869-15	1869-CS	1869-39
12-10 AWG	1969-BP	1969-15	1969-16	1969-39