

Wire Connectors



Closed End

To apply, simply insert pre-stripped wires into connector and crimp. Holds wires firmly even in vibration. For use with stranded wire only.

Gauge	Mini Packs	50 PCS	100 PCS	1000 PCS
22-18 AWG	1166-BP 9 PCS	1166-15	1166-CS	1166-M
16-14 AWG	1266-BP 9 PCS	1266-15	1266-CS	1266-M
12-10 AWG	1366-BP 6 PCS	1366-15	1366-36	1366-M
8 AWG	4066-PR 2 PCS	4066-15	4066-C	4066-M



Closed End - Sealed

In environments where corrosion and/or vibration are a problem, the Closed-End Connector can be used to replace wire nuts. Tubing has an active adhesive that seals between multiple wires. Makes a permanent connection.

Chrysler MS-DB56 CAN 3686, Ford ESB-M97D56A1

Gauge	2 PCS	5 PCS	100 PCS
22-14 AWG	1566-12	1566-14	1566-36
18-10 AWG	1567-12	1567-14	1567-36



Lever-Nut Connector

No twist, push wire connectors for solid and stranded copper wire. They hold each wire individually, eliminating loose connections. No more twisting and taping required. Simply strip the wire, push up lever, insert wire and push down on lever.

Conductors	Gauge	10 PCS	100 PCS
2	28-12 AWG	1631-14	1631-36
3		1633-14	1633-36
5		1637-14	1637-36



Push Wire 2 Conductor

No twist, push wire connectors for solid and stranded copper wire. Clear housing means you can see the firm connection. They hold each wire individually, eliminating loose connections. No more twisting and taping required. Simply strip the wire, insert the conductor and you're finished. The integrated test port allows for continuity testing without re-insertion.

Gauge	3 PCS	10 PCS	100 PCS
16-12 AWG Stranded	1632-13	1632-14	1632-C
18-12 AWG Solid			



Push Wire 3 Conductor

No twist, push wire connectors for solid and stranded copper wire. Clear housing means you can see the firm connection. They hold each wire individually, eliminating loose connections. No more twisting and taping required. Simply strip the wire, insert the conductor and you're finished. The integrated test port allows for continuity testing without re-insertion.

Gauge	2 PCS	10 PCS
14-10 AWG Stranded & Solid	1639-12	1639-14



Push Wire 4 Conductor

No twist, push wire connectors for solid and stranded copper wire. Clear housing means you can see the firm connection. They hold each wire individually, eliminating loose connections. No more twisting and taping required. Simply strip the wire, insert the conductor and you're finished. The integrated test port allows for continuity testing without re-insertion.

Gauge	3 PCS	10 PCS	100 PCS
16-12 AWG Stranded	1634-13	1634-14	1634-C
18-12 AWG Solid			



Push Wire 6 Conductor

No twist, push wire connectors for solid and stranded copper wire. Clear housing means you can see the firm connection. They hold each wire individually, eliminating loose connections. No more twisting and taping required. Simply strip the wire, insert the conductor and you're finished. The integrated test port allows for continuity testing without re-insertion.

Gauge	2 PCS	10 PCS	100 PCS
16-12 AWG Stranded	1636-13	1636-14	1636-C
18-12 AWG Solid			



Push Wire 8 Conductor

No twist, push wire connectors for solid and stranded copper wire. Clear housing means you can see the firm connection. They hold each wire individually, eliminating loose connections. No more twisting and taping required. Simply strip the wire, insert the conductor and you're finished. The integrated test port allows for continuity testing without re-insertion.

Gauge	2 PCS	10 PCS
16-12 AWG Stranded	1638-13	1638-14
18-12 AWG Solid		



Push Wire Fixing Carrier

Push wire connectors not included.

1 PC	100 PCS
1630-11	1630-36



Wire Caps

Colour coded models cover common construction wire ranges. Ribbed cap provides positive grip for fast and easy installation. Narrow design allows more room in tight boxes. Deep, wide throated skirt protects against flash-over and turn back strands. Fixed square spring provides more secure gripping on conductors.

Description	Mini Packs	25 PCS	50 PCS	100 PCS	JARS	1000 PCS
300V Grey	1601-BP 12 PCS	1601-14	1601-15	1601-CS	1601-57 750 PCS	1601-M
300V Blue	1602-BP 12 PCS	1602-14	1602-15	1602-CS	1602-57 500 PCS	1602-39
600V Orange	1603-BP 10 PCS	1603-CS	1603-15	1603-36	1603-57 250 PCS	1603-39
600V Yellow	1604-BP 8 PCS	1604-CS	1604-15	1604-36	1604-57 150 PCS	
		15 PCS				
600V Red	1605-BP 3 PCS	1605-CS	1605-15	1605-36	1605-57 100 PCS	



Winged Wire Caps

Colour coded models cover common construction wire ranges. Winged cap provides positive grip for fast and easy installation. Narrow design allows more room in tight boxes. Deep, wide throated skirt protects against flash-over and turn back strands. Fixed square spring provides more secure gripping on conductors.

Description	Mini Packs	10 PCS	100 PCS
600V Yellow	1620-13 5 PCS	1620-14	1620-36
600V Red	1621-13 4 PCS	1621-14	1621-36
600V Blue	1622-13 3 PCS	1622-14	1622-36



IDC Connector

Self-stripping electrical connector with sealant filling. The sealant filling helps to protect against corrosion due to moisture. No wire stripping is required. Simply insert wires and press down with pliers.

Gauge	2 PCS	10 PCS	100 PCS
22-14 AWG	1640-12	1640-14	1640-36