

TEW Wire Rated 105°C 600V

Meets UL, CSA, MTW, TEW, TW, AWM, 1015/1230/1345 specifications. UL/CSA PVC insulated single conductor wire. Multi-rated for internal wiring of appliances and equipment. Bare copper construction.



TEW Wire 



10 AWG			.180 Outside Diameter		105/30 Stranding			
Length	Black	Blue			Green	Red	White	
100'	8010-0-C	8010-1-C			8010-3-C	8010-5-C	8010-6-C	
1000'	8010-0-M	8010-1-M			8010-3-M	8010-5-M	8010-6-M	
12 AWG			.156 Outside Diameter		65/30 Stranding			
Length	Black	Blue			Green	Red	White	
100'	8012-0-C	8012-1-C			8012-3-C	8012-5-C	8012-6-C	
1000'	8012-0-M	8012-1-M			8012-3-M	8012-5-M	8012-6-M	
14 AWG			.138 Outside Diameter		41/30 Stranding			
Length	Black	Blue	Brown	Green	Orange	Red	White	Yellow
25'	8014-0-44	8014-1-44		8014-3-44	8014-4-44	8014-5-44	8014-6-44	8014-7-44
100'	8014-0-C	8014-1-C	8014-2-C	8014-3-C	8014-4-C	8014-5-C	8014-6-C	8014-7-C
1000'	8014-0-M	8014-1-M	8014-2-M	8014-3-M	8014-4-M	8014-5-M	8014-6-M	8014-7-M
16 AWG			.123 Outside Diameter		26/30 Stranding			
Length	Black	Blue	Brown	Green	Orange	Red	White	Yellow
25'	8016-0-44	8016-1-44		8016-3-44	8016-4-44	8016-5-44	8016-6-44	8016-7-44
100'	8016-0-C	8016-1-C	8016-2-C	8016-3-C	8016-4-C	8016-5-C	8016-6-C	8016-7-C
1000'	8016-0-M	8016-1-M	8016-2-M	8016-3-M	8016-4-M	8016-5-M	8016-6-M	8016-7-M
18 AWG			.112 Outside Diameter		16/30 Stranding			
Length	Black	Blue	Brown	Green	Orange	Red	White	Yellow
25'	8018-0-44	8018-1-44		8018-3-44	8018-4-44	8018-5-44	8018-6-44	8018-7-44
100'	8018-0-C	8018-1-C	8018-2-C	8018-3-C	8018-4-C	8018-5-C	8018-6-C	8018-7-C
1000'	8018-0-M	8018-1-M	8018-2-M	8018-3-M	8018-4-M	8018-5-M	8018-6-M	8018-7-M

SXL Cross-Linked Polyethylene Wire Rated 125°C 60V DC/25V AC

Special purpose automotive wire for circuit wiring where higher heat resistance is a requirement. Meets SAE J1128, Ford ESB-MIL 123A and Chrysler MS-5919 specifications.



SXL Wire 



10 AWG		.191 Outside Diameter		19/23 Stranding			
Length	Black			Green	Red	White	
100'	8510-0-C			8510-3-C	8510-5-C	8510-6-C	
12 AWG		.161 Outside Diameter		19/25 Stranding			
Length	Black	Blue	Brown	Green	Red	White	Yellow
100'	8512-0-C	8512-1-C	8512-2-C	8512-3-C	8512-5-C	8512-6-C	8512-7-C
14 AWG		.138 Outside Diameter		19/27 Stranding			
Length	Black	Blue	Brown	Green	Red	White	Yellow
100'	8514-0-C	8514-1-C	8514-2-C	8514-3-C	8514-5-C	8514-6-C	8514-7-C
1000'	8514-0-29	8514-1-29	8514-2-29	8514-3-29	8514-5-29	8514-6-29	8514-7-29
16 AWG		.119 Outside Diameter		19/29 Stranding			
Length	Black	Blue	Brown	Green	Red	White	Yellow
100'	8516-0-C	8516-1-C	8516-2-C	8516-3-C	8516-5-C	8516-6-C	8516-7-C
1000'	8516-0-29	8516-1-29	8516-2-29	8516-3-29	8516-5-29	8516-6-29	8516-7-29
18 AWG		.107 Outside Diameter		16/30 Stranding			
Length	Black	Blue		Green	Red	White	
100'	8518-0-C	8518-1-C		8518-3-C	8518-5-C	8518-6-C	
1000'	8518-0-29	8518-1-29		8518-3-29	8518-5-29	8518-6-29	

