

Boat Cable Wire Rated 105°C Dry / 75°C Wet 600V

Single conductor electro-tinned wire is ideal for use in the high corrosive environment of marine applications. Electro-tinned copper strands increase corrosion protection. Extremely flexible for easy routing for various applications, and is easier to solder than bare copper. UL listed 1426, meets DOT & Coast Guard specifications for electrical systems. Flame retardant PVC insulation is highly resistant to water, oil, grease, gasoline, and other damaging solvents.



1 Conductor

10 AWG	.190 Outside Diameter / 105/30 Stranding			
Colour	10'	100'	500'	1000'
Black	9010-0-44	9010-0-26	9010-0-28	9010-0-29
Blue	9010-1-44	9010-1-26	9010-1-28	9010-1-29
Dark Blue	9010-D1-44	9010-D1-26	9010-D1-28	9010-D1-29
Brown	9010-2-44	9010-2-26	9010-2-28	9010-2-29
Tan	9010-L2-44	9010-L2-26	9010-L2-28	9010-L2-29
Green	9010-3-44	9010-3-26	9010-3-28	9010-3-29
Dark Green	9010-D3-44	9010-D3-26	9010-D3-28	9010-D3-29
Orange	9010-4-44	9010-4-26	9010-4-28	9010-4-29
Red	9010-5-44	9010-5-26	9010-5-28	9010-5-29
White	9010-6-44	9010-6-26	9010-6-28	9010-6-29
Yellow	9010-7-44	9010-7-26	9010-7-28	9010-7-29
Grey	9010-8-44	9010-8-26	9010-8-28	9010-8-29
Purple	9010-9-44	9010-9-26	9010-9-28	9010-9-29
Pink	9010-44	9010-26	9010-28	9010-29


12 AWG	.162 Outside Diameter / 65/30 Stranding			
Colour	10'	100'	500'	1000'
Black	9012-0-44	9012-0-26	9012-0-28	9012-0-29
Blue	9012-1-44	9012-1-26	9012-1-28	9012-1-29
Dark Blue	9012-D1-44	9012-D1-26	9012-D1-28	9012-D1-29
Brown	9012-2-44	9012-2-26	9012-2-28	9012-2-29
Tan	9012-L2-44	9012-L2-26	9012-L2-28	9012-L2-29
Green	9012-3-44	9012-3-26	9012-3-28	9012-3-29
Dark Green	9012-D3-44	9012-D3-26	9012-D3-28	9012-D3-29
Orange	9012-4-44	9012-4-26	9012-4-28	9012-4-29
Red	9012-5-44	9012-5-26	9012-5-28	9012-5-29
White	9012-6-44	9012-6-26	9012-6-28	9012-6-29
Yellow	9012-7-44	9012-7-26	9012-7-28	9012-7-29
Grey	9012-8-44	9012-8-26	9012-8-28	9012-8-29
Purple	9012-9-44	9012-9-26	9012-9-28	9012-9-29
Pink	9012-44	9012-26	9012-28	9012-29

14 AWG	.138 Outside Diameter / 41/30 Stranding			
Colour	25'	100'	500'	1000'
Black	9014-0-44	9014-0-26	9014-0-28	9014-0-29
Blue	9014-1-44	9014-1-26	9014-1-28	9014-1-29
Dark Blue	9014-D1-44	9014-D1-26	9014-D1-28	9014-D1-29
Brown	9014-2-44	9014-2-26	9014-2-28	9014-2-29
Tan	9014-L2-44	9014-L2-26	9014-L2-28	9014-L2-29
Green	9014-3-44	9014-3-26	9014-3-28	9014-3-29
Dark Green	9014-D3-44	9014-D3-26	9014-D3-28	9014-D3-29
Orange	9014-4-44	9014-4-26	9014-4-28	9014-4-29
Red	9014-5-44	9014-5-26	9014-5-28	9014-5-29
White	9014-6-44	9014-6-26	9014-6-28	9014-6-29
Yellow	9014-7-44	9014-7-26	9014-7-28	9014-7-29
Grey	9014-8-44	9014-8-26	9014-8-28	9014-8-29
Purple	9014-9-44	9014-9-26	9014-9-28	9014-9-29
Pink	9014-44	9014-26	9014-28	9014-29

16 AWG	.122 Outside Diameter / 26/30 Stranding			
Colour	25'	100'	500'	1000'
Black	9016-0-44	9016-0-26	9016-0-28	9016-0-29
Blue	9016-1-44	9016-1-26	9016-1-28	9016-1-29
Dark Blue	9016-D1-44	9016-D1-26	9016-D1-28	9016-D1-29
Brown	9016-2-44	9016-2-26	9016-2-28	9016-2-29
Tan	9016-L2-44	9016-L2-26	9016-L2-28	9016-L2-29
Green	9016-3-44	9016-3-26	9016-3-28	9016-3-29
Dark Green	9016-D3-44	9016-D3-26	9016-D3-28	9016-D3-29
Orange	9016-4-44	9016-4-26	9016-4-28	9016-4-29
Red	9016-5-44	9016-5-26	9016-5-28	9016-5-29
White	9016-6-44	9016-6-26	9016-6-28	9016-6-29
Yellow	9016-7-44	9016-7-26	9016-7-28	9016-7-29
Grey	9016-8-44	9016-8-26	9016-8-28	9016-8-29
Purple	9016-9-44	9016-9-26	9016-9-28	9016-9-29
Pink	9016-44	9016-26	9016-28	9016-29

Fusible Link Wire

Fusible links are not rated in amps like fuses because each installation is unique & designed to meet specific circuit protection. Opens circuit when extreme overload occurs. Used to repair factory installed fusible links. Original length & gauge must match exactly. Fusible link should be 4 gauges smaller than circuit. CAUTION: DO NOT substitute ordinary wire for fusible links. DO NOT replace fuses with fusible link wire. Highly technical calculations are required to determine the correct length and gauge of fusible links.



Install Packs

Each pack includes:
12" Fusible Link
2 Butt Connectors
1 Ring Connector



Spools

12 AWG	14 AWG	16 AWG	18 AWG
8612-BP	8614-BP	8616-BP	8618-BP

Gauge	Stranding	10'	15'
12 AWG	19/27	8612-RL	
14 AWG	19/29		8614-RL
16 AWG	16/30		8616-RL
18 AWG	10/30		8618-RL

