

Specialty Convoluted Split Loom

Slit for easy insertion of wires, yet the slit remains basically closed when the tubing is bent or twisted.



Flame Retardant Polypropylene V2

Flexible flame retardant polypropylene tubing holds groups of wire in position. With blue stripping to identify its flame retardant rating. Rated -40°C to 135°C. UL94-V2



High Temperature Nylon

Flexible nylon tubing holds groups of wire in position. Nylon 6 co-polymer. With grey stripping to identify its high temperature rating. Rated -40°C to 149°C (300°F).



Blue stripping identifies Flame Retardance



Grey stripping identifies High Temperature Rating

I.D.	100' Spool	Box
1/4"	5150-26	5150-45 3200'
3/8"	5151-26	5151-45 1800'
1/2"	5152-26	5152-45 1100'
3/4"	5153-26	5153-45 500'
1"		5154-45 300'

I.D.	100' Spool	Box
1/4"	5160-26	5160-45 3200'
3/8"	5161-26	5161-45 1900'
1/2"	5162-26	5162-45 1100'
5/8"	5159-26	5159-45 800'
3/4"	5163-26	5163-45 550'
1"	5164-26	5164-45 300'
	10' Kit	
1/4", 3/8", 1/2", 3/4"	5185-91	

Loom Accessories & Tools



Tee Fittings

Fittings are measured by convoluted tubing diameter.

Left	Center	Right	2 PCS	10 PCS
3/8"	3/8"	3/8"	5130-12	5130-34
1/2"	1/2"	1/2"	5131-12	5131-34
3/4"	3/8"	3/4"	5132-12	5132-34
3/4"	1/2"	3/4"	5135-12	5135-34



Wire Insertion Tools for Split Loom

Description	1 PC
1/4" to 7/16"	806-11
1/2" to 5/8"	807-11
3/4" to 7/8"	808-11
1" to 1-1/4"	809-11
Kit (1 Each of Size)	810-91

Spiral Wrap

Insulates and protects wire assemblies. Strong grip due to torsion cut and memory of plastic. Useful on long continuous runs where many leads are required. Permits wire and hose break-outs in any orientation. Easily removed and re-applied. Retains its strength under repeated flexing & binding. Ends can be secured with tie wraps.

Rated 94°C max.



Black



Natural

I.D.	Bundle Range	Thickness	Small Pack	100'
1/8"	1/16" to 1/4"	.032	5118-0-44 10'	5118-0-C
1/4"	3/16" to 2"	.035	5120-0-44 10'	5120-0-C
3/8"	5/16" to 3"	.052	5121-0-44 10'	5121-0-C
1/2"	3/8" to 4"	.052	5122-0-44 10'	5122-0-C
3/4"	3/4" to 5"	.065	5123-0-44 5'	5123-0-C
1"	1" to 7"	.095	5124-0-44 5'	5124-0-C

I.D.	Bundle Range	Thickness	Small Pack	100'
1/8"	1/16" to 1/4"	.032	5118-PK 10'	5118-C
1/4"	3/16" to 2"	.035	5120-PK 10'	5120-C
3/8"	5/16" to 3"	.052	5121-PK 10'	5121-C
1/2"	3/8" to 4"	.052	5122-PK 10'	5122-C
3/4"	3/4" to 5"	.065	5123-PK 5'	5123-C
1"	1" to 7"	.095	5124-PK 5'	5124-C