

## Expandable Braided Loom

A versatile bundling & protection solution for your wires, cables and hoses with style. Used in electronics, marine & industrial wire harnessing applications where cost efficiency & durability are critical. Easy to install, light weight, flexible and UV resistant. Cuts easily with a hot knife. Chemically & organically inert.

Conforms to FMVSS 302. Rated -75°C to 125°C. Melt Point: 230°C




Black



Natural

Minimum	Nominal	Maximum	100' Spool
1/8"	1/4"	7/16"	<b>8404-0-26</b>
3/16"	3/8"	5/8"	<b>8405-0-26</b>
1/4"	1/2"	3/4"	<b>8406-0-26</b>
1/2"	3/4"	1-1/4"	<b>8407-0-26</b>

Minimum	Nominal	Maximum	100' Spool
1/8"	1/4"	7/16"	<b>8404-26</b>
3/16"	3/8"	5/8"	<b>8405-26</b>
1/4"	1/2"	3/4"	<b>8406-26</b>
1/2"	3/4"	1-1/4"	<b>8407-26</b>



Blue



Red

Minimum	Nominal	Maximum	100' Spool
1/8"	1/4"	7/16"	<b>8404-1-26</b>
3/16"	3/8"	5/8"	<b>8405-1-26</b>
1/4"	1/2"	3/4"	<b>8406-1-26</b>
1/2"	3/4"	1-1/4"	<b>8407-1-26</b>

Minimum	Nominal	Maximum	100' Spool
1/8"	1/4"	7/16"	<b>8404-5-26</b>
3/16"	3/8"	5/8"	<b>8405-5-26</b>
1/4"	1/2"	3/4"	<b>8406-5-26</b>
1/2"	3/4"	1-1/4"	<b>8407-5-26</b>

## Wrap-able Split Braided Tubing

A unique split, semi-rigid braided construction makes it the ideal solution for situations where ease of installation is of primary importance. The lateral split allows the tube to open up to accommodate a wide variety of bundling requirements. The semi-rigid braid configuration simply closes around the entire installation without the need for any additional fasteners (velcro, tape, etc.). The 10mil braid is lightweight, quiet and flexible. 25% edge overlap (at nominal diameter) allows coverage around inline plugs, connectors and splices. It will bend to a tight radius without distorting or splitting open and unlike full rigid tubing, will not impair or affect the flexibility of harnesses. Cut & abrasion resistant. Cuts easily with a hot knife. Chemically inert and halogen free. Rated -75°C to 125°C



Black



Nominal Diameter	Small Pack	100'
1/8"	<b>8423-0-44</b> 10'	<b>8423-0-26</b>
1/4"	<b>8424-0-44</b> 10'	<b>8424-0-26</b>
1/2"	<b>8426-0-44</b> 10'	<b>8426-0-26</b>
3/4"	<b>8427-0-44</b> 5'	<b>8427-0-26</b>

## Fabric Heat Shrink Tubing

The woven construction makes these extremely flexible and resistant to trapping moisture, heat and humidity.



Fabric Heat Shrink Tubing

Shrink Temperature: 135°C  
Temperature Rating: -40°C to 125°C

Description	Unshrunk Diameter	Shrunk Diameter	10'	25'
3/4" Black	20 mm	10 mm	<b>8391-34</b>	<b>8391-24</b>
1 1/2" Black	40 mm	20 mm	<b>8393-34</b>	<b>8393-24</b>
2" Black	50 mm	25 mm	<b>8394-34</b>	<b>8394-24</b>
2-3/4"	70 mm	35 mm	<b>8396-34</b>	<b>8396-24</b>

