





Tape



33' All Weather PVC  
33 ft. / Roll (10 m)
Rated -10°C to 80°C, 600V
3/4" Wide x 0.007" Thick



Colour	1 Roll	10 Rolls	300 Rolls
Black	3433-0-E	3433-0-RL	3433-0-35



Double Wide 66' All Weather PVC  
66 ft. / Roll (20 m)
Rated -10°C to 80°C, 600V
1 1/2" Wide x 0.007" Thick



Colour	1 Roll	10 Rolls
Black	3464-0-E	3464-0-RL



22' Self-Bonding Rubber Splice Tape  
Self-amalgamating, low voltage rubber tape.
For use as primary insulation at no more than 600V. It easily conforms to irregular shapes and surfaces yielding a void free, electrically stable build-up. It is compatible with all extruded dielectric cable insulations. Rated 600V
3/4" Wide x 0.030" Thick
22 ft. / Roll (6.7 m)



1 Roll	10 Rolls
3465-E	3465-RL



66' All Weather PVC  
66 ft. / Roll (20 m)
Rated -10°C to 80°C, 600V
3/4" Wide x 0.007" Thick

Colour	1 Roll	10 Rolls	100 Rolls	200 Rolls
Black	3466-0-E	3466-0-RL	3466-0-C	3466-0-35
Blue	3466-1-E	3466-1-RL		
Green	3466-3-E	3466-3-RL		
Orange	3466-4-E	3466-4-RL		
Red	3466-5-E	3466-5-RL		
White	3466-6-E	3466-6-RL		
Yellow	3466-7-E	3466-7-RL		



66' Cold Weather Flame Retardant Tape  
66 ft. / Roll (20 m)
Gloss surface finish.
Rated -18°C to 105°C, 600V
3/4" Wide x 0.0085" Thick

Colour	1 Roll	10 Rolls
Black	3468-31	3468-37



40' PTFE Thread Seal Tape 
Made of 100% pure virgin PTFE. Easier to wrap, even in the cold. Offers a clean, quick and highly effective means of sealing threaded pipe fittings in the engineering, chemical and electrical industries. It may be used with pipes of any material and with any medium, including oils, solvents and the strongest alkalis, acids and other corrosive chemicals.
Rated -190°C to 280°C
40 ft. / Roll (12.2 m) 1/2" Thick

1 Roll	10 Rolls
3467-E	3467-34



Liquid Electrical Tape

Thousands of uses around the home, boat, RV as well as industrial uses. Forms a protective, waterproof, UV resistant, dielectric coating. Prevents corrosion on wires and terminals. Patented, UL® tested, fast drying formula. Dries to touch in about 10 minutes and fully cures in 24 hours.

1 Case of 6 x 4oz Cans
9040-35

Performance™

Performance Self Fusing Tape

Ideal solution for any application. Self fusing tape provides a water-proof seal and is a great insulator with high dielectric strength. Uses include: Marine, automotive, home and industrial. Great for sealing our air and water, insulating electrical connections or colour coding and increasing the grip of tools. No adhesive, tape fuses upon itself when wrapped to form a permanent airtight, and watertight bond.



Colour	1 Roll	10 Rolls
Black	3469-0-31	3469-0-34
Red	3469-5-31	3469-5-34

