

### Heavy Duty Stackable Ring Connectors

Locks in numerous positions. The exceptional lock ensures terminals will adhere to one another to resist vibration. Colour coded to identify correct die and number of crimps.



#### Butt Splice

Electro-Tin Plated Copper Alloy 110  
3/8" Stud



Gauge	Colour	1 PC	5 PCS
1/0 AWG	Black	3811-11	3811-34
2/0 AWG	Orange	3821-11	3821-34
3/0 AWG	Purple	3831-11	3831-34
4/0 AWG	Yellow	3841-11	3841-34



#### Single Barrel

Electro-Tin Plated Copper Alloy 110  
3/8" Stud



Gauge	Colour	1 PC	5 PCS	100 PCS
4 AWG	Grey	3804-11	3804-34	
2-1 AWG	Pink	3801-11	3801-34	
1/0 AWG	Black	3810-11	3810-34	
2/0 AWG	Orange	3820-11	3820-34	
3/0 AWG	Purple	3830-11	3830-34	3830-36
4/0 AWG	Yellow	3840-11	3840-34	

### 45° Tubular Lug Rings



NEW!

Plated <sup>RoHS</sup>

Electro-Tin Plated Copper from Tubular Stock  
Used for Heavy Duty wiring.  
Solder or Crimp  
600V

Tin Melting Point: 232°C

Gauge	Stud	10 PCS	100 PCS
4 AWG	1/4"	4251-34	4251-36
	5/16"	4252-34	4252-36
	3/8"	4253-34	4253-36
	1/2"	4254-34	4254-36
2 AWG	1/4"	4351-34	4351-36
	5/16"	4352-34	4352-36
	3/8"	4353-34	4353-36
1 AWG	1/2"	4354-34	4354-36
	1/4"	4851-34	4851-36
	5/16"	4852-34	4852-36
3/8"		4853-34	4853-36
	1/2"	4854-34	4854-36
	1/0 AWG	1/4"	4451-34
5/16"		4452-34	4452-36
	3/8"	4453-34	4453-36
	1/2"	4454-34	4454-36
		5 PCS	
2/0 AWG	5/16"	4552-34	4552-36
	3/8"	4553-34	4553-36
	1/2"	4554-34	4554-36
3/0 AWG	1/4"	4651-34	4651-36
	5/16"	4652-34	4652-36
	3/8"	4653-34	4653-36
	1/2"	4654-34	4654-36
4/0 AWG	5/16"	4752-34	4752-36
	3/8"	4753-34	4753-36
	1/2"	4754-34	4754-36

### Heavy Duty Starter / Battery Lug Connectors

Highest conductivity and greatest crank force. Heavier wall thickness and wider pads. Longer barrels for more crimping area. Pure Copper Electro-Tin Plated for reducing corrosion. Colour coded to identify correct die and number of crimps.



#### Butt Splice



Gauge	Colour	1 PC	5 PCS	100 PCS
4 AWG	Grey	5300-11	5300-PK	5300-36
2-1 AWG	Pink	5308-11	5308-PK	5308-36
1/0 AWG	Black	5313-11	5313-PK	5313-36
2/0 AWG	Orange	5316-11	5316-PK	5316-36
3/0 AWG	Purple	5319-11	5319-PK	5319-36
4/0 AWG	Yellow	5322-11	5322-PK	5322-36

### Solid Barrel Lug Connectors



Insulated <sup>RoHS</sup>

Electro-Tin Plated Copper Alloy 110  
Nylon Insulated

Gauge	2 PCS	25 PCS	100 PCS
8 AWG	4000N-12	4000N-PK	4000N-C
6 AWG	4100N-12	4100N-PK	4100N-C



Non-Insulated <sup>RoHS</sup>

Electro-Tin Plated Copper Alloy 110

Gauge	2 PCS	25 PCS	100 PCS
8 AWG	4000-PR	4000-PK	4000-C
6 AWG	4100-PR	4100-PK	4100-C
	10 PCS		
4 AWG	4200-PR	4200-PK	4200-C
2 AWG	4300-PR	4300-PK	4300-C
1/0 AWG	4400-PR	4400-PK	4400-C
5 PCS			
2/0 AWG	4500-PR	4500-PK	4500-C
3/0 AWG	4600-PR	4600-PK	
4/0 AWG	4700-PR	4700-PK	

