



# PICO®

## Welding Cable Specifications Sheet

Part #	Colour	Gauge	Stranding	Insulation Thickness	Nominal O.D.
<b>8058</b>	Black	4/0 AWG	19/106/.010	0.080"	0.720"
<b>8058-5</b>	Red	4/0 AWG	19/106/.010	0.080"	0.720"
<b>8057</b>	Black	3/0 AWG	19/81/.010	0.080"	0.625"
<b>8057-5</b>	Red	3/0 AWG	19/81/.010	0.080"	0.625"
<b>8059</b>	Black	2/0 AWG	19/65/.010	0.080"	0.586"
<b>8059-5</b>	Red	2/0 AWG	19/65/.010	0.080"	0.586"
<b>8060</b>	Black	1/0 AWG	19/52/.010	0.080"	0.533"
<b>8060-5</b>	Red	1/0 AWG	19/52/.010	0.080"	0.533"
<b>8061</b>	Black	1 AWG	12/65/.010	0.080"	0.503"
<b>8061-5</b>	Red	1 AWG	12/65/.010	0.080"	0.503"
<b>8062</b>	Black	2 AWG	12/52/.010	0.060"	0.420"
<b>8062-5</b>	Red	2 AWG	12/52/.010	0.060"	0.420"
<b>8064</b>	Black	4 AWG	7/52/.010	0.060"	0.348"
<b>8064-5</b>	Red	4 AWG	7/52/.010	0.060"	0.348"
<b>8065</b>	Black	6 AWG	7/37/.010	0.060"	0.320"
<b>8065-5</b>	Red	6 AWG	7/37/.010	0.060"	0.320"

### Notes

- Jacket Temperature: -50°C to 105°C
- Voltage Rating DC: 600V
- RoHS Compliant
- Oil Resistant
- Resistant to Flame
- Cables meet the UL VW-1 flame test outlined in UL1581
- SAE J1127 Stranding
- Jacket Materials - EPDM
- 100% Copper