



PICO[®]

Automotive Primary Wire Specifications Sheet

| Part # Range | Gauge | Nominal OD | Min Wall Thickness | Wire Stranding | Minimum Cmils |
|----------------------|--------|------------|--------------------|----------------|---------------|
| 8108 - 8108-6 | 8 AWG | .215" | 0.026" | 19 x 21 | 14,810 |
| 8110 - 8110-9 | 10 AWG | .174" | 0.022" | 19 x 23 | 9,343 |
| 8112 - 8112-9 | 12 AWG | .142" | 0.018" | 19 x 25 | 5,833 |
| 8114 - 8114-9 | 14 AWG | .117" | 0.016" | 19 x 27 | 3,702 |
| 8116 - 8116-9 | 16 AWG | .102" | 0.016" | 19 x 29 | 2,336 |
| 8118 - 8118-9 | 18 AWG | .095" | 0.016" | 16 x 30 | 1,537 |
| 8120 - 8120-7 | 20 AWG | .085" | 0.016" | 11 x 30 | 1,072 |
| 8022 - 8022-7 | 22 AWG | .077" | 0.016" | 7 x30 | 681 |

- Jacket Temperature: -40°C to 80°C
- Voltage Rating DC (AC): 60V (25V)
- ROHS Compliant
- Conductors meet SAE J1128 & SAE J378 Type GPT
- Jacket Materials - Polyvinylchloride (PVC)