

Bonded Parallel Wire Rated 80°C 60V

All copper strand core. Designed especially for RVs, boats and utility trailers. Conductors meet SAE J1128 specifications.




Gauge	O.D.	Stranding	25'	100'	1000'
14/2 AWG	.117 x .234	19/27	8139-PK	8139-C	8139-M
16/2 AWG	.102 x .204	19/29	8138-PK	8138-C	8138-29
18/2 AWG	.095 x .190	16/30	8144-PK	8144-C	8144-M



Gauge	O.D.	Stranding	25'	100'	1000'
14/3 AWG	.117 x .351	19/27	8140-PK	8140-C	8140-29
16/3 AWG	.102 x .306	19/29	8142-PK	8142-C	8142-29



Gauge	O.D.	Stranding	25'	100'	1000'
14/4 AWG	.117 x .468	19/27	8141-PK	8141-C	8141-29
16/4 AWG	.102 x .408	19/29	8143-PK	8143-C	8143-29



Gauge	O.D.	Stranding	100'
16/5 AWG	.102 x .510	19/29	8135-26

Rubber Cord Type SJ00W -40°C to 90°C & Electrical Plugs

Extra flexible EPDM rubber insulation and CPE jacket. CSA/UL certified for indoor and outdoor use in dry locations. Ideal for flex applications in harsh environments where the highest degree for oil resistant and extended service life are essential. Meets CSA FT-2. Meets or exceeds all applicable requirements of UL-62, CSA Standard 22.2 No. 49, MSHA flame resistance for mining applications. Complies with military spec JC-580B, NEC article 400, OSHA acceptable.



Gauge	Stranding	50'	100'	250'	1000'
14/2 AWG	41/30	8902-B	8902-C	8902-27	8902-M
16/2 AWG	23/30	8901-B	8901-C	8901-27	
18/2 AWG	16/30	8900-B	8900-C	8900-27	



Gauge	Stranding	50'	100'	250'	1000'
10/3 AWG	104/30	8907-25	8907-26	8907-27	
12/3 AWG	65/30	8906-25	8906-26	8906-27	
14/3 AWG	41/30	8905-B	8905-C	8905-27	8905-M
16/3 AWG	23/30	8904-B	8904-C	8904-27	
18/3 AWG	16/30	8903-B	8903-C	8903-27	



Industrial Grade Electrical Plugs

S-15R NEMA configuration.

Description	1 PC	10 PCS
Female	8956-11	8956-34
Male	8957-11	8957-34
Pair	8958-91	



Hippo Hinge Electrical Plugs

Description	1 PC	10 PCS
Female	8952-11	8952-34
Male	8953-11	8953-34



Industrial Grade Black Electrical Plugs

Black Electrical Plugs and Sockets work with SJ/SJT/SJE/S Cord types. Solid Brass blades provide excellent conductivity. Rugged PVC and Thermoplastic Rubber construction ensures lasting durability in the toughest environments.

Description	1 PC	10 PCS
Female	8954-11	8954-34
Male	8955-11	8955-34

Mechanics Wire



18GA Mechanics Wire

General purpose soft annealed mechanics stove pipe tie-wire. Also known as baling wire. Used in an agricultural setting and industrial setting for everything from mending fences to manually binding square bales of hay, straw, or cut grass.

50'	75'	330'
8122-13	8122-PK	8122-RL

