

## 16 AWG Bonded Parallel Wire Specifications Sheet

<b>NOTES</b>				
<b>Part Number</b>	<b>8135</b>	<b>8143</b>	<b>8142</b>	<b>8138</b>
<b>Gauge</b>	16/5	16/4	16/3	16/2
<b>Nominal OD</b>	0.102" x 0.510"	0.102" x 0.408"	0.102" x 0.306"	0.102" x 0.204"
<b>Minimum Wall Thickness</b>	0.016"	0.016"	0.016"	0.016"
<b>Stranding</b>	19 x 29	19 x 29	19 x 29	19 x 29
<b>Minimum Cmils</b>	2,336	2,336	2,336	2,336
<b>Jacket Temperature</b>	80°C	80°C	80°C	80°C
<b>Jacket Temperature</b>	-40°C	-40°C	-40°C	-40°C
<b>Voltage Rating DC</b>	60 V	60 V	60 V	60 V
<b>Voltage Rating AC</b>	25 V	25 V	25 V	25 V
<b>Colours</b>	White/Brown/ Yellow/Green/Blue	White/Brown/ Yellow/Green	Brown/Yellow/ Green	Red/Black

- RoHS Compliant
- Conductors meet SAE J1128 & J378 Type GPT
- Jacket material - Polyvinylchloride (PVC)

