

## **Battery Harnesses, and Jumpers**



# Premium Quality Battery Jumpers 2 Position

1/O AWGBattery Cable, Tinned Copper Stranding, (UL), Extra HD Stackable Lugs, Tin Plated, Shrink & Seal Protected Connections.

Description	Length	1 PC	10 PCS	
Negative	8"	6500-31	6500-34	
Positive	8″	6501-31	6501-34	



## Overmolded Battery Jumpers

2 Position

Made with 2/0 AWG battery cable, attached protective caps seal the connection. Fits up to 3/8" studs.

Description	1 PC
Negative	6610-31
Positive	6611-31



#### **Premium Quality Battery Jumpers**

3 Postion

1/0 AWG Battery Cable, Tinned Copper Stranding, (UL), Extra HD Stackable Lugs, Tin Plated, Shrink & Seal Protected Connections.

3 '				
Description	Length	1 PC	10 PCS	
Negative	17"	6502-31	6502-34	
Positive	17"	6503-31	6503-34	



### **Overmolded Battery Jumpers**

3 Position

Made with 2/0 AWG battery cable, attached protective caps seal the connection. Fits up to  $3/8^{\prime\prime}$  studs.

Description	1 PC
Negative	6612-31
Positive	6613-31



### **Premium Quality Battery Jumpers**

**4 Position** 

1/0 AWG Battery Cable, Tinned Copper Stranding, (UL), Extra HD Stackable Lugs, Tin Plated, Shrink & Seal Protected Connections.

Description	Length	1 PC	10 PCS	
Negative	26"	6504-31	6504-34	
Positive	26"	6505-31	6505-34	





#### **Overmolded Battery Jumpers**

4 Position

Made with 2/0 AWG battery cable, attached protective caps seal the connection. Fits up to 3/8" studs.


Description	1 PC
Negative	6614-31
Positive	6615-31




**Battery to Battery**For series hook-up.

Description	Length	1 PC	Description	Length	1 PC	10 PCS
1 AWG	8"	6138-11	4 AWG	8"	6248-BP	
1 AWG	12"	6139-11	4 AWG	15"	6250-BP	
1 AWG	15"	6140-11	1 AWG	12"	6244-BP	
2/0 AWG	8"	6142-11	2/0 AWG	10"	6247-11	6247-34
2/0 AWG	12"	6143-11				

# **Cable Hookups for Multiple Battery Clusters**





4 Battery Group. Mounted together.

