

Battery Harnesses, and Jumpers Continued



Battery Harness Assemblies 2/0 AWG

Make your own harness system. Designed to link Group 31 batteries in series and parallel layouts. Meets or exceeds OEM quality. Pre-assembled harnesses save time and cost of building cables from component parts. Connect array to your existing cables. Length is measured stud-center to stud-center.



Standard Plated Lug	Length	1 PC	10 PCS
Negative	8-1/2"	850N-31	850N-34
Positive	8-1/2"	850P-31	850P-34
Negative	17"	851N-31	851N-34
Positive	17"	851P-31	851P-34
Negative	24"	857N-31	
Positive	24"	857P-31	
Stackable Plated Lug	Length	1 PC	10 PCS
Negative	8-1/2"	855N-E	855N-34
Positive	8-1/2"	855P-E	855P-34
Negative	17"	856N-E	856N-34
Positive	17"	856P-E	856P-34



2-Battery Stud to Power Harnesses

2/0 AWG, 7"

Description	1 PC
Negative	6307-31
Positive	6308-31



3-Battery Stud to Power Harnesses

2/0 AWG, 14"

Description	1 PC
Negative	6314-31
Positive	6315-31

Cable Splice - Battery Cables

Made of 100% copper conductor with gravity cast antimonial lead universal terminals. Full-gauge stranded copper core is flexible for easy installation and allows maximum current for quick starting. Wire meets SAE standards. For fast convenient replacement of hard to reach cables. Replaces corroded portion, not the entire cable. Ideal for automotive, truck, farm and industrial applications.



OE Style Quick Connect Cable Splice

Part No.	Description	Qty
6184-11	Dual Top Post	1



OE Style Quick Connect Cable Splice

Part No.	Description	Qty
6186-11	Side Post	1



OE Style Quick Connect Cable Splice

Part No.	Description	Qty
6185-11	Top Post	1

Ground Straps

Solves electrical problems by grounding charging systems. Maximum protection against corrosion for farm, commercial vehicles, and off-road applications.



Clamp-Lug Ground Straps

Description	Length	1 PC
2 AWG 9"	9"	6254-BP
2 AWG 14"	14"	6255-BP
2 AWG 19"	19"	6283-11



Lug-Lug Ground Straps

Description	Length	1 PC	10 PCS
11 AWG	8'	6170-11	6170-34
11 AWG	20"	6171-11	
4 AWG	9"	6256-BP	
4 AWG	12"	6257-BP	6257-34
4 AWG	24"	6284-BP	



Ground Strap Cable

Description	25 FT	100 FT
10 AWG	8070-24	8070-26
4 AWG	8071-24	
2 AWG	8072-24	

Battery Cables

Made of 100% copper conductor with gravity cast antimonial lead universal terminals. Full-gauge stranded copper core is flexible for easy installation and allows maximum current for quick starting. Wire meets SAE standards.



Ford F Series Diesel 2/0 AWG

Designed for a Dual Battery System. Features Heavy Duty Lead Die Cast Terminal Ends, Protective Terminal Insulator Guards and Self-Extinguishing Cable Loom.

Description	1 PC
9.6'	6149-31

