

Rubber Insulated & Vinyl Dipped Clamps

Secures all types of wiring to the body or frame of all mobile equipment. Flexible neoprene cushion holds lines firmly while protecting them from shock, abrasion and vibration.



Rubber Insulated Aluminum

Metal Width: 1/2"
Mount Hole: 1/4"

I.D.	2 PCS	Mini Packs	100 PCS	1000 PCS
1/4"	7314-BP	7314-PK 20 PC	7314-C	7314-M
3/8"	7315-BP	7315-PK 20 PC	7315-C	7315-M
1/2"	7316-BP	7316-PK 20 PC	7316-C	7316-M
5/8"	7317-BP	7317-PK 20 PC	7317-C	7317-M
3/4"	7318-12	7318-PK 20 PC	7318-C	7318-M
7/8"	7319-12	7319-PK 17 PC	7319-C	7319-M
1"	7320-12	7320-PK 13 PC	7320-C	7320-M
1-1/8"	7321-12	7321-PK 10 PC	7321-C	7321-39
1-1/4"	7322-12	7322-PK 10 PC	7322-C	7322-M
1-3/8"	7323-12	7323-PK 7 PC	7323-C	7323-39
1-1/2"		7324-PK 5 PC	7324-C	7324-M
1-5/8"		7325-PK 5 PC	7325-C	7325-39
1-3/4"		7326-PK 5 PC	7326-C	7326-39
2"		7327-PK 5 PC	7327-C	7327-39
2-1/2"		7328-PK 3 PC	7328-C	7328-39
3"		7329-PK 3 PC	7329-C	7329-39
4"		7330-PK 3 PC	7330-C	



Rubber Insulated Zinc Plated Steel

Metal Width: 5/8"
Mount Hole: 3/8"

I.D.	Mini Packs	100 PCS
1/4"	7514-PK 20 PC	7514-C
3/8"	7515-PK 20 PC	7515-C
1/2"	7516-PK 20 PC	7516-C
5/8"	7517-PK 20 PC	7517-C
3/4"	7518-PK 20 PC	7518-C
7/8"	7519-PK 17 PC	7519-C
1"	7520-PK 13 PC	7520-C
1-1/4"	7522-PK 10 PC	7522-C
1-1/2"	7524-PK 5 PC	7524-C
1-3/4"	7526-PK 5 PC	7526-C
2"	7527-PK 5 PC	7527-C
2-1/2"	7528-PK 3 PC	7528-C



Rubber Insulated Stainless Steel

Metal Width: 1/2"
Mount Hole: 1/4"

I.D.	Mini Packs	100 PCS
1/4"	7414-34 20 PC	7414-36
3/8"	7415-34 20 PC	7415-36
1/2"	7416-34 20 PC	7416-36
5/8"	7417-34 20 PC	7417-36
3/4"	7418-34 20 PC	7418-36
1"	7420-34 13 PC	7420-36
1-1/4"	7422-34 10 PC	7422-36
1-1/2"	7424-34 5 PC	7424-36



Vinyl Dipped Zinc Plated Steel

Metal Width: 1/2"
Mount Hole: 1/4"

I.D.	Mini Packs	100 PCS
1/4"	7614-34 20 PC	7614-36
3/8"	7615-34 20 PC	7615-36
1/2"	7616-34 20 PC	7616-36
3/4"	7618-34 20 PC	7618-36
1"	7620-34 13 PC	7620-36
1-1/4"	7622-34 10 PC	7622-36
1-1/2"	7624-34 5 PC	7624-36
2"	7627-34 5 PC	7627-36

Nylon Cable Clamps



Light Duty Natural Nylon Cable Clamps



Mount Hole: 5.2 mm (.205")
Thickness: 1.3 mm (.051")
Width: 9.5 mm (.374")
UL94-V2
Temperature Rating: 85°C (185°F)

Diameter	Closed	Mini Packs	100 PCS	1000 PCS
1/8"	.115"	7118LN-BP 18 PC	7118LN-C	7118LN-39
3/16"	.172"	7119LN-BP 15 PC	7119LN-C	7119LN-M
1/4"	.234"	7120LN-BP 14 PC	7120LN-C	7120LN-M
5/16"	.297"	7121LN-BP 14 PC	7121LN-C	7121LN-39
3/8"	.359"	7122LN-BP 14 PC	7122LN-C	7122LN-M
7/16"	.422"	7123LN-BP 14 PC	7123LN-C	7123LN-M
1/2"	.484"	7124LN-BP 14 PC	7124LN-C	7124LN-M



Heavy Duty Black Nylon Cable Clamps



Mount Hole: 5.2 mm (.205")
Thickness: 1.5 mm (.059")
Width: 12.7 mm (.500")
UL94-V2
Temperature Rating: 85°C (185°F)

Diameter	Closed	25 PCS	100 PCS	1000 PCS
3/16"	.172"	7119HNO-34	7119HNO-36	7119HNO-39
1/4"	.234"	7120HNO-34	7120HNO-36	7120HNO-39
3/8"	.359"	7122HNO-34	7122HNO-36	7122HNO-39
1/2"	.484"	7124HNO-34	7124HNO-36	7124HNO-39

