

Performance Cable Ties



Performance — Extreme Duty

A true all weather cable tie. Seven times more UV resistant than the standard tie. Enhanced flexibility and strength in extreme heat and extreme cold weather or low humidity applications. Increased UV protection material rated at -40°C (-40°F) per ISO 180. Tested for application performance at -20°C (-4°F). Made with a special additive that prevents drying and breaking in cold, low humidity conditions. The very best Cable Ties we offer.



Description	Bundle	Tensile	25 PCS	50 PCS	100 PCS
7.5" UV Black	1.875"	50 lb.	7295-34		7295-36
11" UV Black	3.062"	50 lb.	7296-34		7296-36
14" UV Black	4"	50 lb.	7297-34		7297-36
15" UV Black	4.06"	120 lb.	7298-34		7298-36
24" UV Black	7.2"	175 lb.		7299-35	

Standard Cable Ties



One piece self-locking cable ties. No metal barbs. Tie locks in place automatically. Snip off excess tail. General purpose nylon 6-6 is a weather resistant grade suitable for use in most practical applications at a continuous temperature up to 185°F. Rated UL94-V2, MIL-M-20693B  

Description	CSA Approved	Military Spec.	Bundle	Thickness	Width	Tensile	25 PCS	50 PCS	100 PCS	1000 PCS
4" Natural			0.805"	0.040"	0.095"	18 lb.	7063-PK		7063-C	7063-M
4" UV Black			0.805"	0.040"	0.095"	18 lb.	7063-0-PK		7063-0-C	7063-0-M
5.8" Natural		MS 3367-5-9	1.25"	0.05"	0.142"	40 lb.	7065-PK		7065-C	7065-M
5.8" UV Black		MS 3367-5-0	1.25"	0.05"	0.142"	40 lb.	7065-0-PK		7065-0-C	7065-0-M
6" Natural						18 lb.	7064-34		7064-36	7064-39
6" Black						18 lb.	7064-0-34		7064-0-36	7064-0-39
7.5" Natural		MS 3367-5-9	2"	0.054"	0.142"	50 lb.	7066-PK		7066-C	7066-M
7.5" UV Black		MS 3367-1-0	2"	0.054"	0.142"	50 lb.	7066-0-PK		7066-0-C	7066-0-M
8" Natural			2"	0.076"	0.3"	120 lb.	7066HD-PK		7066HD-C	7066HD-M
8" UV Black			2"	0.076"	0.3"	120 lb.	7066HD0-PK		7066HD0-C	7066HD0-M
8" Natural		MS 3367-5-9	2.375"	0.049"	0.140"	40 lb.	7066L-PK		7066L-C	7066L-M
8" UV Black		MS 3367-5-0	2.375"	0.049"	0.140"	40 lb.	7066L0-PK		7066L0-C	7066L0-M
8.1" Natural						18 lb.	7088-34		7088-36	7088-39
8.1" UV Black						18 lb.	7088-0-34		7088-0-36	7088-0-39
9" Natural			2.17"		0.492"	250 lb.	7140HD-PK		7140HD-C	
11" Natural		MS 3367-7-9	3"	0.054"	0.142"	50 lb.	7067-PK		7067-C	7067-M
11" UV Black		MS 3367-7-0	3"	0.054"	0.142"	50 lb.	7067-0-PK		7067-0-C	7067-0-M
14" Natural		MS 3367-2-9	4"	0.054"	0.142"	50 lb.	7068-PK		7068-C	7068-M
14" UV Black		MS 3367-2-0	4"	0.054"	0.142"	50 lb.	7068-0-PK		7068-0-C	7068-0-M
15" Natural		MS 3367-3-9	4.06"	0.076"	0.3"	120 lb.	7068HD-PK		7068HD-C	7068HD-M
15" UV Black		MS 3367-3-0	4.06"	0.076"	0.3"	120 lb.	7068HD0-PK		7068HD0-C	7068HD0-M
17" UV Black			5.08"	0.005"	0.185"	50 lb.			7289-36	
18" UV Black			5.25"		0.305"	120 lb.	7291-34		7291-36	
22" UV Black			5.7"		0.492"	250 lb.	7141HD0-PK		7141HD0-C	
24" UV Black			7"		0.305"	120 lb.	7293-34		7293-36	
25.2" Natural		MS 3367-10-9	7.18"	0.09"	0.34"	175 lb.	7069-PK	7069-35		7069-M
25.2" UV Black		MS 3367-10-0	7.18"	0.09"	0.34"	175 lb.	7069-0-PK	7069-0-35		7069-0-M
30" Natural			8"		0.3"	120 lb.	7070-PK	7070-35		
30" UV Black			8"		0.3"	120 lb.	7070-0-PK	7070-0-35		
37.2" Natural		MS 3367-13-9	11"	0.09"	0.34"	175 lb.	7150HD-PK	7150HD-35		
37.2" UV Black		MS 3367-13-0	11"	0.09"	0.34"	175 lb.	7150HD0-PK	7150HD0-35		
48.5" Natural		MS 3367-16-9	14.5"	0.09"	0.34"	175 lb.	7152HD-PK	7152HD-35		
48.5" UV Black		MS 3367-16-0	14.5"	0.09"	0.34"	175 lb.	7152HD0-PK	7152HD0-35		

