

Ring Connectors Continued



Crimp-Solder-Seal Ring Connectors RoHS

Crimped for mechanical reliability. Soldered for superior strength and conductivity. Sealed for maximum durability. Meets or exceeds the most stringent OEM standards.



Gauge	Ring Size	5 PCS	25 PCS	100 PCS
22-18 AWG	#10	3505-14	3505-15	3505-36
16-14 AWG	#10	3605-BP	3605-15	3605-36
	3/8"	3609-BP	3609-15	3609-36
12-10 AWG	#10	3705-BP	3705-15	3705-36
	1/4"	3706-BP	3706-15	3706-36
	3/8"	3709-BP	3709-15	3709-36



Solder-Shrink RoHS

Translucent, adhesive lined polyolefin tubing allows visual inspection, prevents wire corrosion and provides a waterproof seal. Easy installation with pre-measured solder. A soldered electrical connection provides superior current flow and tensile strength.

Gauge	Ring Size	5 PCS	25 PCS	100 PCS
22-18 AWG	#6	6703-BP	6703-15	6703-36
	#8	6704-BP	6704-15	6704-36
	#10	6705-BP	6705-15	6705-36
	1/4"	6706-BP	6706-15	6706-36
	3/8"	6709-14	6709-15	6709-36
16-14 AWG	#6	6803-14	6803-15	6803-36
	#8	6804-BP	6804-15	6804-36
	#10	6805-BP	6805-15	6805-36
	1/4"	6806-BP	6806-15	6806-36
	3/8"	6809-BP	6809-15	6809-36
12-10 AWG	#10	6905-BP	6905-15	6905-36
	1/4"	6906-BP	6906-15	6906-36
	3/8"	6909-BP	6909-15	6909-36
	1/2"	6913-BP	6913-15	6913-36



High Temperature RoHS

Recommended for use in ovens, motors, light fixtures and other applications where other connectors would corrode or melt. 900°F (482°C)

Gauge	Ring Size	Mini Packs	50 PCS	100 PCS
22-18 AWG	#6	9103-BP 10 PCS	9103-15	9103-16
	#10	9105-BP 10 PCS	9105-15	9105-16
	1/4"	9106-BP 7 PCS	9106-15	9106-16
16-14 AWG	#6	9203-BP 9 PCS	9203-15	9203-CS
	#10	9205-BP 9 PCS	9205-15	9205-CS
	1/4"	9206-BP 6 PCS	9206-15	9206-CS
12-10 AWG	#6	9303-BP 6 PCS	9303-15	9303-CS
	#10	9305-BP 6 PCS	9305-15	9305-CS
	1/4"	9306-BP 5 PCS	9306-15	9306-CS
	3/8"	9309-BP 5 PCS	9309-15	9309-CS



Non-Insulated Brazed Seam



Bare, Brazed Seam - Same high quality construction as the Butted Seam Terminals, except it features a brazed seam. Unique process bonds the seam to assure the maximum strength in wire termination.

Gauge	Ring Size	Mini Packs	50 PCS	100 PCS	1000 PCS
22-18 AWG	#6	2603-13 10 PCS	2603-15	2603-CS	2603-39
	#8	2604-13 10 PCS	2604-15	2604-CS	2604-39
	#10	2605-13 10 PCS	2605-15	2605-CS	
16-14 AWG	#6	2703-BP 8 PCS	2703-15	2703-CS	2703-M
	#8	2704-BP 8 PCS	2704-15	2704-CS	2704-M
	#10	2705-BP 8 PCS	2705-15	2705-CS	2705-M
	1/4"	2706-BP 5 PCS	2706-15	2706-CS	2706-39
	5/16"	2708-BP 5 PCS	2708-15	2708-CS	
	3/8"	2709-BP 5 PCS	2709-15	2709-CS	
12-10 AWG	#6	2803-BP 6 PCS	2803-15	2803-16	
	#8	2804-BP 6 PCS	2804-15	2804-16	
	#10	2805-BP 6 PCS	2805-15	2805-16	2805-M
	1/4"	2806-BP 4 PCS	2806-15	2806-16	
	5/16"	2808-BP 4 PCS	2808-15	2808-16	
	3/8"	2809-BP 4 PCS	2809-15	2809-16	
	1/2"	2813-BP 3 PCS	2813-15	2813-16	



Non-Insulated - Butted Seam



Bare, Butted Seam - One piece, annealed, pure electrolytic copper construction with electro-tin plating for corrosion resistance. Deep internal serrations promote firm wire grip for maximum tensile strength.

Gauge	Ring Size	Mini Packs	50 PCS	100 PCS	1000 PCS
22-18	#6	2303-BP 16 PCS	2303-15	2303-CS	2303-M
	#8	2304-BP 16 PCS	2304-15	2304-CS	2304-M
	#10	2305-BP 16 PCS	2305-15	2305-CS	2305-M
	1/4"	2306-BP 11 PCS	2306-15	2306-CS	2306-39
	5/16"		2308-15	2308-CS	
	3/8"		2309-15	2309-CS	2309-39
16-14	#6	2403-BP 14 PCS	2403-15	2403-CS	
	#8	2404-BP 14 PCS	2404-15	2404-CS	2404-39
	#10	2405-BP 14 PCS	2405-15	2405-CS	2405-M
	1/4"	2406-BP 10 PCS	2406-15	2406-CS	2406-39
	5/16"	2408-BP 10 PCS	2408-15	2408-CS	
	3/8"	2409-BP 10 PCS	2409-15	2409-CS	
12-10	#8	2504-BP 8 PCS	2504-15	2504-CS	
	#10	2505-BP 8 PCS	2505-15	2505-CS	2505-39
	1/4"	2506-BP 6 PCS	2506-15	2506-CS	2506-39
	5/16"	2508-BP 6 PCS	2508-15	2508-CS	
	3/8"	2509-BP 6 PCS	2509-15	2509-CS	2509-39
	1/2"	2513-BP 5 PCS	2513-15	2513-16	



Flat Ring Connectors RoHS

Gauge	Ring Size	5 PCS	50 PCS	100 PCS
16-14 AWG	#10	2416-BP	2416-15	2416-CS
12-10 AWG	#10	2516-BP	2516-15	